

LONKING PRODUCTS


LONKING (FUJIAN) INTERNATIONAL TRADE CO.,LTD.
Add:26 Minyi Road,Xinqiao,Songjiang Industrial Zone,Shanghai
Tel: +86-21-3760 2242 E-mail:export@lonking.cn
http://www.lonkinggroup.com



WHEEL LOADER		OW: Operating weight. BC: Bucket capacity. RL: Rated load. ENG: Engine power.				
3.0T		LG833H/CDM833 (Tier 2)	OW(kg)	BC (m³)	RL(kg)	ENG(kW)
		CDM833 (Tier 3, LCVm)	10300	1.7	3000	92
3.5T		CDM835 (Tier 2, Chinese engine)	OW(kg)	BC (m³)	RL(kg)	ENG(kW)
		CDM835 (Tier 2, Imported brand engine)	11620	1.8	3500	105
4.0T		CDM835 (Wet Axles)	11620	1.8	3500	97
		CDM843 (Tier 2)	11750	1.8	3500	105
5.0T		CDM853 (Width=2550mm)	OW(kg)	BC (m³)	RL(kg)	ENG(kW)
		CDM853 (Tier 2)	16400	3.0	5000	162
6.5T		LG855H (Tier 2 +Pilot)	OW(kg)	BC (m³)	RL(kg)	ENG(kW)
		LG855H (Tier 2+Mechanical)	17200	3.0	5000	162
7T		ZL50HC (Tier 2)	OW(kg)	BC (m³)	RL(kg)	ENG(kW)
		ZL50HCS (Tier 3,Heavy-duty)	17300	3.0	5000	162
5.5T		CDM856 (Tier 2+Mechanical shift)	OW(kg)	BC(m³)	RL(kg)	ENG(kW)
		CDM856 (Tier 2+Electric control shift)	17300	3.0	5500	162
6.5T		CDM856 (Tier 3+LCVM)	17300	3.0	5500	154
		LG863H (Tier 2)	OW(kg)	BC (m³)	RL(kg)	ENG(kW)
7T		LG863H (Tier 3)	21900	4.2	6500	175
		CDM866 (Tier 3, Automatic shift)	22100	4.2	6500	178
Stone Fork Loader		LG876H (Tier 3, Automatic shift)	OW(kg)	BC (m³)	RL(kg)	ENG(kW)
		LGFT18 (Tier 3)	23500	5.2	7000	199
Electric Wheel Loader		LGFT28 (Tier 3)	OW(kg)	Fork Size (mm)	RL(kg)	ENG(kW)
		CDM856HE (282/350kwH)	23900	1400×200×120	19000	162
		CDM866HE (350/423kwH)	29560	1520x240x140	28000	178
			OW(kg)	BC(m³)	RL(kg)	ENG(kW)
			17800	3.0	5500	90
			21900	4.2	6500	110

MINI WHEEL LOADER		OW: Operating weight. BC: Bucket capacity. RL: Rated load. ENG: Engine power.				
Series N - 1.2T		CDM926N (Tier 2 + Pilot)	OW(kg)	BC(m³)	RL(kg)	ENG(kW)
			6380	1.2	2000	75
Series N - 1.5T		CDM932N (Tier 2)	OW(kg)	BC(m³)	RL(kg)	ENG(kW)
		CDM932NG (Tier 23, LCVm)	5230	0.8	1500	65
Series N - 2T		CDM915N (Euro V)	5230	0.8	1500	60
			4450	0.75	1500	45
Series D - 1.6T		CDM936N (Tier 2)	OW(kg)	BC(m³)	RL(kg)	ENG(kW)
		CDM936N (Tier 3)	6380	1.2	2000	75
Series D - 1.8T		CDM936N (Agricultural)	6380	1.2	2000	85
			6450	1.2	2000	75
Underground Loader		CDM816D (Tier 2)	OW(kg)	BC(m³)	RL(kg)	ENG(kW)
			5500	0.95	1600	55
Rough Terrain Lift Truck		CDM818D (Tier 2)	OW(kg)	BC(m³)	RL(kg)	ENG(kW)
		CDM818D (Tier 3, LCVm)	5600	1.05	1800	63
			OW(kg)	BC(m³)	RL(kg)	ENG(kW)
			6200	1.20	2000	66.2
			6400	1.20	2000	66.2
			OW(kg)	BC(m³)	RL(kg)	ENG(kW)
			5130	550	2500	60
			6990	550	3000	85

SKID STEER LOADER		OW: Operating weight. ENG: Engine power. BC: Bucket capac RL: Rated load.				
303 Series		CDM303T(Euro V)	OW(kg)	BC(m³)	RL(kg)	ENG(kW)
			1640	0.15	344	18.5
307 Series		CDM307 (Chinese engine)	OW(kg)	BC(m³)	RL(kg)	ENG(kW)
		CDM307 (Imported engine)	2800	0.43	760	36.7
308 Series		CDM307 (Euro V)	2700	0.43	752	36
			2800	0.43	752	44.8
312 Series		CDM308 (Chinese engine)	OW(kg)	BC(m³)	RL(kg)	ENG(kW)
		CDM308 (Imported engine)	2900	0.48	899	36.7
		CDM308 (Euro V)	2900	0.48	899	36
			2900	0.48	861	44.8
			OW(kg)	BC(m³)	RL(kg)	ENG(kW)
			3500	0.54	1230	55
			3500	0.54	1230	63
			3500	0.54	1230	55.8

HYDRAULIC EXCAVATOR		OW: Operating weight. RP: Rated power. BC: Bucket capacity. TS: Travel Speed.				
Mini Excavator		CDM6010 Euro V	OW(kg)	BC (m³)	RL(kg)	ENG(kW)
			1010	0.022	7.2	7.2
2T		CDM6016 Euro V	OW(kg)	BC (m³)	RL(kg)	ENG(kW)
			1010	0.022	7.2	7.2
2.5-3.5T		CDM6020 Canopy Tier 3 / Euro V	OW(kg)	BC (m³)	RL(kg)	ENG(kW)
			1860	0.04	13.4	13.4
		CDM6020 Cabin Tier 4F / Euro V	OW(kg)	BC (m³)	RL(kg)	ENG(kW)
			1860	0.04	13.4	13.4
Small Excavator		CDM6025 Tier 4F / Euro V	OW(kg)	BC (m³)	RL(kg)	ENG(kW)
			2650	0.08	14.6	14.6
6-6.5T		CDM6035 Tier 4F / Euro V	OW(kg)	BC (m³)	RL(kg)	ENG(kW)
			3850	0.11	18.1	18.1
7.5-8T		CDM6060 Tier 3, Chinese engine/Imported brand engine	OW(kg)	BC (m³)	RL(kg)	ENG(kW)
			5850	0.25	36.8 / 36.2	36.8 / 36.2
		CDM6065 Tier 3	OW(kg)	BC (m³)	RL(kg)	ENG(kW)
			6050	0.25	46.3	46.3
Medium Excavator		CDM6075 Tier 3, Chinese engine/Imported brand engine	OW(kg)	BC (m³)	RL(kg)	ENG(kW)
			7680	0.28	45/46.3	45/46.3
13-20T		CDM6080 Tier 3	OW(kg)	BC (m³)	RL(kg)	ENG(kW)
			8000	0.3	56.5	56.5
22T		CDM6135/CDM6150 Tier 3	OW(kg)	BC (m³)	RL(kg)	ENG(kW)
			13600/14000	0.56	74/86	74/86
		CDM6205 Tier 3, 118kW for Russia	OW(kg)	BC (m³)	RL(kg)	ENG(kW)
			21100	0.85	129/118	129/118
22T		CDM6225 Tier 2, Optional Width 2540mm	OW(kg)	BC (m³)	RL(kg)	ENG(kW)
			21800	1.1	112	112
		CDM6225 Tier 3, Chinese engine / Imported brand engine	OW(kg)	BC (m³)	RL(kg)	ENG(kW)
			21800	1.1	129/124	129/124
22-24T		CDM6245 Tier 3, Optional-Independent cooling	OW(kg)	BC (m³)	RL(kg)	ENG(kW)
			25800	1.3	145	145
		CDM6225H Tier 2, For Forest use	OW(kg)	BC (m³)	RL(kg)	ENG(kW)
			24500	1.3	112	112
Large Excavator		CDM6240 Tier 2	OW(kg)	BC (m³)	RL(kg)	ENG(kW)
			22600	1.16	133	133
26-33T		CDM6266 Tier 3, Independent cooling	OW(kg)	BC (m³)	RL(kg)	ENG(kW)
			26800	1.55	145	145
37-50T		CDM6336 Tier 2 / Tier 3	OW(kg)	BC (m³)	RL(kg)	ENG(kW)
			32800	1.6	241/212	241/212
70-100T		CDM6225H Tier 2, Long Reach, 15m	OW(kg)	BC (m³)	RL(kg)	ENG(kW)
			23500/24000	0.5/0.4	3.6/5.2	3.6/5.2
		CDM6396 Tier 2 / Tier 3	OW(kg)	BC (m³)	RL(kg)	ENG(kW)
			39300	1.9	241/212	241/212
		CDM6490/CDM6550F Tier 3	OW(kg)	BC (m³)	RL(kg)	ENG(kW)
			50500/51000	3.4/5.3	3.4/5.3	3.4/5.3
			OW(kg)	BC (m³)	RL(kg)	ENG(kW)
			6900	0.43	760	36.7
			2700	0.43	752	36
			2800	0.43	752	44.8
			OW(kg)	BC (m³)	RL(kg)	ENG(kW)
			2900	0.48	899	36.7
			2900	0.48	899	36
			2900	0.48	861	44.8
			OW(kg)	BC (m³)	RL(kg)	ENG(kW)
			3500	0.54	1230	55
			3500	0.54	1230	63
			3500	0.54	1230	55.8

WHEEL EXCAVATOR		OW: Operating weight. RP: Rated power. BC: Bucket capacity. TS: Travel Speed.				
7-12T		CDM6070W/CDM6075W Tier 2/Tier 3	OW(kg)	BC (m³)	RL(kg)	ENG(kW)
			6000/7000	0.48/55	97	73.5
15-22T		CDM6125W Tier 3	OW(kg)	BC (m³)	RL(kg)	ENG(kW)
			10000	0.4	30	30
		CDM6150W Tier 3	OW(kg)	BC (m³)	RL(kg)	ENG(kW)
			13500	0.5	97	73.5
		CDM6225W Tier 3, Width=2550mm	OW(kg)	BC (m³)	RL(kg)	ENG(kW)
			22500	1	112	112
			OW(kg)	BC (m³)	RL(kg)	ENG(kW)
			28000	0.5	1230	63
			3500	0.54	1230	55.8

FORK LIFT		OW: Operating weight. RC: Rated capacity. LC: Load Center. PT: Power type.				
Engine Forklift			OW(kg)	RC(kg)	LC (mm)	PT
1.5T		FD15T	2680	1500	500	Diesel
GLT-Series		LG15GLT	2900	1500	500	LPG
2-3.8T			OW(kg)	RC(kg)	LC (mm)	PT
LG-Series		LG20DT	3250	2000	500	Diesel
		LG25DT	3600	2500	500	Diesel
		LG30DT	4160	3000	500	Diesel
		LG35DT	4630	3500	500	Diesel
FD-Series		FD20T	3420	2000	500	Diesel
		FD25T	3770	2500	500	Diesel
		FD30T	4220	3000	500	Diesel
		FD35T	4650	3500	500	Diesel
		FD38T	5000	3800	500	Diesel
GLT-Series		LG20GLT	3310	2000	500	LPG
		LG25GLT	3550	2500	500	LPG
		LG30GLT	4180	3000	500	LPG
		LG35GLT	4650	3500	500	LPG
4-Compact 5T			OW(kg)	RC(kg)	LC (mm)	PT
LG40DTIV		6530	4000	500	Diesel	
LG45DTIV		6760	4500	500	Diesel	
LG50DTIV		7100	5000	500	Diesel	
5-7T			OW(kg)	RC(kg)	LC (mm)	PT
LG50DT		8320	5000	600	Diesel	
LG60DT		8940	6000	600	Diesel	
LG70DT		9540	7000	600	Diesel	
7.5T			OW(kg)	RC(kg)	LC (mm)	PT
LG75DT		10330	7500	600	Diesel	
LG75DTG		10330	7500	600	Diesel	
6-8T for Container Loading			OW(kg)	RC(kg)	LC (mm)	PT
LG50DT		8750	6000	600	Diesel	
LG60DT		10200	8000	600	Diesel	
LG70DT		11900	10000	600	Diesel	
8.5-10T			OW(kg)	RC(kg)	LC (mm)	PT
LG85DT		12150	8500	600	Diesel	
LG100DT		13250	10000	600	Diesel	
12-16T			OW(kg)	RC(kg)	LC (mm)	PT
LG120DT		15300	12000	600	Diesel	
LG135DT		18000	13500	600	Diesel	
LG160DT(A)		23500	16000	900	Diesel	
LG160DT(B)		24000	16000	1200	Diesel	